

GLAMOUR



EN14041



Specifications and tolerances in according EN 1307

EMISSIONI NEGLI AMBIENTI INTERNI



A+ A B C

Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

STAINADVERSE



RECYCLABLE PLASTIC
Licence HCP200392

COSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TUFTING VELLUTO 5/32"	TUFTED CUT PILE 5/32"	TUFTED VELOURS 5/32"	GETUFTED VELOURS 5/32"
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% POLIAMMIDE 6	100% POLYAMIDE 6	100% POLYAMIDE 6	100% POLYAMID 6
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
JUTA SINTETICA	SYNTHETIC JUTE	JUTE SYNTHÉTIQUE	SDR TESTILRUCKEN
PUNTI AL M²	STITCHES PER M²	TOUFFES AU M²	KNOTEN M²
± 100000	± 100000	± 100000	± 100000
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 9.3 mm	± 9.3 mm	± 9.3 mm	± 9.3 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 11.8 mm	± 11.8 mm	± 11.8 mm	± 11.8 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 2000 g/m²	± 2000 g/m²	± 2000 g/m²	± 2000 g/m²
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 2700 g/m²	± 2700 g/m²	± 2700 g/m²	± 2700 g/m²
LARGHEZZA ROTOLO	ROLL WIDTH	LARGEUR DU ROLEAU	BREITE
400 cm	400 cm	400 cm	400 cm
FAMIGLIA TUFTING 1	FAMIGLIA TUFTING 1	FAMIGLIA TUFTING 1	FAMIGLIA TUFTING 1



COMFORT: ★★★★★

BUSINESS WEARABILITY: ★★★☆

DOMESTIC WEARABILITY: ★★★

This product is recyclable.

Colour fastness to light	≥ 5	Thermal resistance m2 K/W	≤ 0,17
Insulation impact noise ΔLw	37 dB	Body voltage walking test kV	≤ 2
Acoustical absorption α _w	0,20		