



PROPERTIES	STANDARDS	OMNISPORTS ACTIVE +
DECLARATION OF PERFORMANCE		
0120-095-DoP-2020-09		
CLASSIFICATION		
Type of floor covering	EN 14904	Heterogeneous indoor floorcoverings
TECHNICAL CHARACTERISTICS		
Total thickness	EN ISO 24346 (EN 428)	8.1mm
Total weight	EN ISO 23997 (EN 430)	4760g/m ²
Width	EN ISO 24341 (EN 426)	2 m
Length	EN ISO 24341 (EN 426)	20.51m
REQUIREMENTS FOR SAFE USE		
Friction	EN 13036-4	80 to 110
Shock absorption	EN 14808	≥35% (P2)
Vertical deformation	EN 14809	P2
Specular gloss	EN ISO 2813	≤30%
TECHNICAL PERFORMANCES		
Vertical ball behaviour	EN 12235	≥95%
Reaction to fire	EN 13501-1	Cfl-s1*
Resistance to wear	EN ISO 5470-1	≤250mg
Resistance to indentation	EN 1516 (Average measured value)	≤0.3mm
Resistance to a rolling load	EN 1569	≤0.5mm
Reduction of impact noise	EN ISO 717-2	21dB
Thermal resistance	EN ISO 10456	Approx. 0.12 m ² K/W Compatible with underfloor heating



* glued and GreenLay™ installation on concrete

Technical data in force as from the date of publication (12/2024).

The values above correspond to laboratory test (no in situ test) and are subject to modifications for the benefit of further improvement.

Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.