

Technical specifications

Showtime meets the requirements of EN1307

Showtime Colour

	Total thickness	ISO 1765	4.9 mm
	Wear layer thickness	ISO 1766	1.6 mm
	Total weight	ISO 8543	1150 g/m ²
	Collection size		17
	Commercial use	EN ISO 10874	Class 32
	Pile composition		100% polyamide
	Pile weight	ISO 8543	280 g/m ²
	Backing		100% recycled polyester
	Roll width		200 cm
	Roll length		± 40 m
	Impact noise reduction	EN ISO 717-2	20 dB
	Sound absorption	EN ISO 354	$\alpha_w = 0,15$ (H)
	Castor chair continuous use	ISO 4918	$r \geq 2,4$
	Colour fastness to light	ISO 105/B02	≥ 6
	Colour fastness to water	ISO 105/E01	$\geq 3-4$
	Colour fastness to rubbing wet	ISO 105-X12	≥ 3
	Colour fastness to Rubbing dry	ISO 105-X12	$\geq 3-4$
	Indoor air emissions: TVOC after 28 days	EN 16516	$\leq 0,1$ mg/m ³
	Recycled content	Needlefelt sheet are manufactured with at least 50% recycled content by weight	
	Installation method		↑↑

Showtime meets the requirements of EN 14041

	Product code	EN 14041:2004	0300721-DoP-010
	Reaction to fire	EN 13501-1	C _s -s1, G, NCS
	Slip resistance	EN 13893	$\mu > 0.30$
	Thermal conductivity	EN 12524	0.06 W/mK
	Body voltage	ISO 6356	< 2.0 kV